

TECHNICAL SPECIFICATIONS

CBP 46 S

Dimensions (mm)	675 x 850 x 2040	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	120	Capacity	40 x 60 cm – 20 pcs	Frequency	50 Hz.
Packaging Dimensions (mm)	735 x 970 x 2160	Insulation Thickness(mm)	70	Power (W)	300
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CBP 46 D

Dimensions (mm)	675 x 850 x 2040	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	123	Capacity	40 x 60 cm – 20 pcs	Frequency	50 Hz.
Packaging Dimensions (mm)	735 x 970 x 2160	Insulation Thickness(mm)	70	Power (W)	500
Interior Temperature °C	-10/-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CBP 68 S

Dimensions (mm)	800 x 980 x 2070	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	140	Capacity	60 x 80 cm— 20 pcs	Frequency	50 Hz.
Packaging Dimensions (mm)	860 x 1150 x 2100	Insulation Thickness(mm)	70	Power (W)	450
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CBP 68 D

Dimensions (mm)	800 x 980 x 2070	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	145	Capacity	60 x 80 cm – 20 pcs	Frequency	50 Hz.
Packaging Dimensions (mm)	860 x 1150 x 2100	Insulation Thickness(mm)	70	Power (W)	850
Interior Temperature °C	-10/-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®