

TECHNICAL SPECIFICATIONS

CSM 260 S

Dimensions (mm)	1600 x 600 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	105	Capacity	150 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1660 x 660 x 750	Insulation Thickness(mm)	50	Power (W)	320
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CSM 260 D

Dimensions (mm)	1600 x 600 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	115	Capacity	150 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1660 x 660 x 750	Insulation Thickness(mm)	50	Power (W)	600
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

TECHNICAL SPECIFICATIONS

CSMG 270 S

Dimensions (mm)	1600 x 700 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	115	Capacity	175 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1660 x 760 x 750	Insulation Thickness(mm)	50	Power (W)	320
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CSMG 270 D

Dimensions (mm)	1600 x 700 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	125	Capacity	175 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1660 x 760 x 750	Insulation Thickness(mm)	50	Power (W)	600
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

TECHNICAL SPECIFICATIONS

CSMG 280 S

Dimensions (mm)	1600 x 800 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	125	Capacity	210 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1660 x 860 x 750	Insulation Thickness(mm)	50	Power (W)	320
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CSMG 280 D

Dimensions (mm)	1600 x 800 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	135	Capacity	210 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1660 x 860 x 750	Insulation Thickness(mm)	50	Power (W)	600
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*