

TECHNICAL SPECIFICATIONS

PRO 260 S

Dimensions (mm)	1425 x 600 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	135	Capacity	220 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1485 x 660 x 1000	Insulation Thickness(mm)	70	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

PRO 260 D

Dimensions (mm)	1425 x 600 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	140	Capacity	220 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1485 x 660 x 1000	Insulation Thickness(mm)	70	Power (W)	620
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

TECHNICAL SPECIFICATIONS

PRO 270 S

Dimensions (mm)	1425 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	140	Capacity	270 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1485 x 760 x 1000	Insulation Thickness(mm)	70	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 270 D

Dimensions (mm)	1425 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	145	Capacity	270 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1485 x 760 x 1000	Insulation Thickness(mm)	70	Power (W)	620
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 280 S

Dimensions (mm)	1425 x 800 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	145	Capacity	320 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1485 x 860 x 1000	Insulation Thickness(mm)	70	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 280 D

Dimensions (mm)	1425 x 800 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	150	Capacity	320 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1485 x 860 x 1000	Insulation Thickness(mm)	70	Power (W)	620
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*