

# TECHNICAL SPECIFICATIONS

## PRO 360 S

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>1890 x 600 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>155</b>               | Capacity                 | <b>340 Lt</b>   | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>1950 x 660 x 1000</b> | Insulation Thickness(mm) | <b>70</b>       | Power (W) | <b>275</b>       |
| Interior Temperature °C   | <b>-2 /+8</b>            | Refrigerant Gas          | <b>R134</b>     |           |                  |

**Optional\***

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## PRO 360 D

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>1890 x 600 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>170</b>               | Capacity                 | <b>340 Lt</b>   | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>1950 x 660 x 1000</b> | Insulation Thickness(mm) | <b>70</b>       | Power (W) | <b>680</b>       |
| Interior Temperature °C   | <b>-10 /-22</b>          | Refrigerant Gas          | <b>R404</b>     |           |                  |

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## PRO 370 S

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>1890 x 700 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>170</b>               | Capacity                 | <b>420 Lt</b>   | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>1950 x 760 x 1000</b> | Insulation Thickness(mm) | <b>70</b>       | Power (W) | <b>275</b>       |
| Interior Temperature °C   | <b>-2 /+8</b>            | Refrigerant Gas          | <b>R134</b>     |           |                  |

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## PRO 370 D

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>1890 x 700 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>185</b>               | Capacity                 | <b>420 Lt</b>   | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>1950 x 760 x 1000</b> | Insulation Thickness(mm) | <b>70</b>       | Power (W) | <b>680</b>       |
| Interior Temperature °C   | <b>-10 /-22</b>          | Refrigerant Gas          | <b>R404</b>     |           |                  |

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## PRO 380 S

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>1890 x 800 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>185</b>               | Capacity                 | <b>500 Lt</b>   | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>1950 x 860 x 1000</b> | Insulation Thickness(mm) | <b>70</b>       | Power (W) | <b>275</b>       |
| Interior Temperature °C   | <b>-2 /+8</b>            | Refrigerant Gas          | <b>R134</b>     |           |                  |

Optional\*

# TECHNICAL SPECIFICATIONS

## PRO 380 D

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>1890 x 800 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>200</b>               | Capacity                 | <b>500 Lt</b>   | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>1950 x 860 x 1000</b> | Insulation Thickness(mm) | <b>70</b>       | Power (W) | <b>680</b>       |
| Interior Temperature °C   | <b>-10 /-22</b>          | Refrigerant Gas          | <b>R404</b>     |           |                  |

Optional\*