

TECHNICAL SPECIFICATIONS

PRO 160 S

Dimensions (mm)	960 x 600 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	115	Capacity	100 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1020 x 660 x 1000	Insulation Thickness(mm)	70	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 160 D

Dimensions (mm)	960 x 600 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	120	Capacity	100 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1020 x 660 x 1000	Insulation Thickness(mm)	70	Power (W)	620
Interior Temperature °C	-10/-22	Refrigerant Gas	R404		

Optional*

TECHNICAL SPECIFICATIONS

PRO 170 S

Dimensions (mm)	960 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	120	Capacity	120 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1020 x 760 x 1000	Insulation Thickness(mm)	70	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

PRO 170 D

Dimensions (mm)	960 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	125	Capacity	120 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1020 x 760 x 1000	Insulation Thickness(mm)	70	Power (W)	620
Interior Temperature °C	-10/-22	Refrigerant Gas	R404		

Optional*

TECHNICAL SPECIFICATIONS

PRO 180 S

Dimensions (mm)	960 x 800 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	125	Capacity	140 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1020 x 860 x 1000	Insulation Thickness(mm)	70	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

PRO 180 D

Dimensions (mm)	960 x 800 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	130	Capacity	140 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1020 x 860 x 1000	Insulation Thickness(mm)	70	Power (W)	620
Interior Temperature °C	-10/-22	Refrigerant Gas	R404		

Optional*