

TECHNICAL SPECIFICATIONS

PRO 260 S-R

Dimensions (mm)	1300 x 600 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	90	Capacity	220 Lt
Packaging Dimensions (mm)	1340 x 660 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-2/+8		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 260 D-R

Dimensions (mm)	1300 x 600 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	95	Capacity	220 Lt
Packaging Dimensions (mm)	1340 x 660 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-10 /-22		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 270 S-R

Dimensions (mm)	1300 x 700 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	100	Capacity	270 Lt
Packaging Dimensions (mm)	1340 x 760 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-2/+8		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 270 D-R

Dimensions (mm)	1300 x 700 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	105	Capacity	270 Lt
Packaging Dimensions (mm)	1340 x 760 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-10 / -22		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 360 S-R

Dimensions (mm)	1770 x 600 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	115	Capacity	340 Lt
Packaging Dimensions (mm)	1810 x 660 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-2/+8		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 360 D-R

Dimensions (mm)	1770 x 600 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	120	Capacity	340 Lt
Packaging Dimensions (mm)	1810 x 660 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-10 / -22		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 370 S-R

Dimensions (mm)	1770 x 700 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	125	Capacity	420 Lt
Packaging Dimensions (mm)	1810 x 760 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-2/+8		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 370 D-R

Dimensions (mm)	1770 x 700 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	130	Capacity	420 Lt
Packaging Dimensions (mm)	1810 x 760 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-10 / -22		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 460 S-R

Dimensions (mm)	2230 x 600 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	135	Capacity	460 Lt
Packaging Dimensions (mm)	2270 x 660 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-2/+8		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 460 D-R

Dimensions (mm)	2230 x 600 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	140	Capacity	460 Lt
Packaging Dimensions (mm)	2270 x 660 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-10/-22		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 470 S-R

Dimensions (mm)	2230 x 700 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	155	Capacity	540 Lt
Packaging Dimensions (mm)	2270 x 760 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-2/+8		

CRYSTAL®

TECHNICAL SPECIFICATIONS

PRO 470 D-R

Dimensions (mm)	2230 x 700 x 850	Stainless Steel Type	AISI 304
Net Weight (Kg)	160	Capacity	540 Lt
Packaging Dimensions (mm)	2270 x 760 x 1000	Insulation Thickness(mm)	50
Interior Temperature °C	-10 / -22		

CRYSTAL®