

TECHNICAL SPECIFICATIONS

STD 700 S

Dimensions (mm)	700 x 840 x 2060	Stainless Steel Type	AISI 304	Voltage*	220/230 V
Net Weight (Kg)	122	Capacity	600 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	760 x 880 x 2140	Insulation Thickness(mm)	70 mm	Power (W)	250
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

STD 700 S-E

Dimensions (mm)	700 x 840 x 2060	Stainless Steel Type	AISI 430	Voltage*	220/230 V
Net Weight (Kg)	122	Capacity	600 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	760 x 880 x 2140	Insulation Thickness(mm)	70 mm	Power (W)	250
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

STD 700 D

Dimensions (mm)	700 x 840 x 2060	Stainless Steel Type	AISI 304	Voltage*	220/230 V
Net Weight (Kg)	125	Capacity	600 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	760 x 880 x 2140	Insulation Thickness(mm)	70 mm	Power (W)	600
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

TECHNICAL SPECIFICATIONS

STD 700 D-E

Dimensions (mm)	700 x 840 x 2060	Stainless Steel Type	AISI 430	Voltage*	220/230 V
Net Weight (Kg)	125	Capacity	600 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	760 x 880 x 2140	Insulation Thickness(mm)	70 mm	Power (W)	600
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*