

TECHNICAL SPECIFICATIONS

PRO-C 260 S

Dimensions (mm)	1200 x 600 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	80	Capacity	125 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1260 x 660 x 750	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

PRO-C 360 S

Dimensions (mm)	1770 x 600 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	115	Capacity	225 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 660 x 750	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

PRO-C 460 S

Dimensions (mm)	2230 x 600 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	145	Capacity	300 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2290 x 660 x 750	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

PRO-C 270 S

Dimensions (mm)	1200 x 700 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	95	Capacity	150 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1260 x 760 x 750	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

PRO-C 370 S

Dimensions (mm)	1770 x 700 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	135	Capacity	270 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 760 x 750	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

PRO-C 470 S

Dimensions (mm)	2230 x 700 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	165	Capacity	370 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2290 x 760 x 750	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*