

TECHNICAL SPECIFICATIONS

STD 360 S

Dimensions (mm)	1770 x 600 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	130	Capacity	340 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 660 x 1000	Insulation Thickness(mm)	50	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

STD 360 D

Dimensions (mm)	1770 x 600 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	135	Capacity	340 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 660 x 1000	Insulation Thickness(mm)	50	Power (W)	680
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

STD 370 S

Dimensions (mm)	1770 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	145	Capacity	420 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 760 x 1000	Insulation Thickness(mm)	50	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

STD 370 D

Dimensions (mm)	1770 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	150	Capacity	420 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 760 x 1000	Insulation Thickness(mm)	50	Power (W)	680
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

STD 360 S-E

Dimensions (mm)	1770 x 600 x 850	Stainless Steel Type	AISI 430	Voltage*	220-230 V
Net Weight (Kg)	130	Capacity	340 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 660 x 1000	Insulation Thickness(mm)	50	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

STD 360 D-E

Dimensions (mm)	1770 x 600 x 850	Stainless Steel Type	AISI 430	Voltage*	220-230 V
Net Weight (Kg)	135	Capacity	340 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 660 x 1000	Insulation Thickness(mm)	50	Power (W)	680
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

TECHNICAL SPECIFICATIONS

STD 370 S-E

Dimensions (mm)	1770 x 700 x 850	Stainless Steel Type	AISI 430	Voltage*	220-230 V
Net Weight (Kg)	145	Capacity	420 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 760 x 1000	Insulation Thickness(mm)	50	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

STD 370 D-E

Dimensions (mm)	1770 x 700 x 850	Stainless Steel Type	AISI 430	Voltage*	220-230 V
Net Weight (Kg)	150	Capacity	420 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1830 x 760 x 1000	Insulation Thickness(mm)	50	Power (W)	680
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*