

# TECHNICAL SPECIFICATIONS

## CHMG 270 SN

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>1430 x 700 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>120</b>               | Capacity                 | <b>270</b>      | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>1490 x 760 x 1000</b> | Insulation Thickness(mm) | <b>50</b>       | Power (W) | <b>350</b>       |
| Interior Temperature °C   | <b>-2/+8</b>             | Refrigerant Gas          | <b>R134</b>     |           |                  |

Optional\*

# TECHNICAL SPECIFICATIONS

## CHMG 370 SN

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>1900 x 700 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>150</b>               | Capacity                 | <b>420</b>      | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>1960 x 760 x 1000</b> | Insulation Thickness(mm) | <b>50</b>       | Power (W) | <b>350</b>       |
| Interior Temperature °C   | <b>-2/+8</b>             | Refrigerant Gas          | <b>R134</b>     |           |                  |

Optional\*

# TECHNICAL SPECIFICATIONS

## CHMG 470 SN

|                           |                          |                          |                 |           |                  |
|---------------------------|--------------------------|--------------------------|-----------------|-----------|------------------|
| Dimensions (mm)           | <b>2360 x 700 x 850</b>  | Stainless Steel Type     | <b>AISI 304</b> | Voltage*  | <b>220-230 V</b> |
| Net Weight (Kg)           | <b>180</b>               | Capacity                 | <b>540</b>      | Frequency | <b>50 Hz.</b>    |
| Packaging Dimensions (mm) | <b>2410 x 760 x 1000</b> | Insulation Thickness(mm) | <b>50</b>       | Power (W) | <b>350</b>       |
| Interior Temperature °C   | <b>-2/+8</b>             | Refrigerant Gas          | <b>R134</b>     |           |                  |

**Optional\***