

TECHNICAL SPECIFICATIONS

CHMG 270- OT ENG

Dimensions (mm)	1430 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	115	Capacity	270 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1490 x 760 x 1000	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CHMG 370- OT ENG

Dimensions (mm)	1900 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	155	Capacity	420 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1960 x 760 x 1000	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CHMG 470- OT ENG

Dimensions (mm)	2360 x 700 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	170	Capacity	540 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2410 x 760 x 1000	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®