

TECHNICAL SPECIFICATIONS

CBS 100 S

Dimensions (mm)	600 x 600 x 810	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	65	Capacity	100 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	660 x 660 x 970	Insulation Thickness(mm)	50	Power (W)	275
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CBS 100 D

Dimensions (mm)	600 x 600 x 810	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	70	Capacity	100 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	660 x 660 x 970	Insulation Thickness(mm)	50	Power (W)	450
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

TECHNICAL SPECIFICATIONS

CBS 150 S

Dimensions (mm)	600 x 700 x 810	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	73	Capacity	150 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	660 x 760 x 970	Insulation Thickness(mm)	50	Power (W)	275
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CBS 150 D

Dimensions (mm)	600 x 700 x 810	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	78	Capacity	150 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	660 x 760 x 970	Insulation Thickness(mm)	50	Power (W)	450
Interior Temperature °C	-2 /+8	Refrigerant Gas	R404		

Optional*