

TECHNICAL SPECIFICATIONS

CPSB3H

Dimensions (mm)	675 x 930 x 2040	Stainless Steel Type (Frame)	AISI 304	Voltage*	220-240 V
Net Weight (Kg)	111	Capacity	3 GN	Frequency	50 Hz.
Packaging Dimensions (mm)	1340 x 800 x 1420			Power (W)	2300
Interior Temperature °C	+30/+90				

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CPSB4H

Dimensions (mm)	800 x 1100 x 2070	Stainless Steel Type (Frame)	AISI 304	Voltage*	220-240 V
Net Weight (Kg)	140	Capacity	4 GN	Frequency	50 Hz.
Packaging Dimensions (mm)	1660 x 800 x 1420			Power (W)	3200
Interior Temperature °C	+30/+90				

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CPSB5H

Dimensions (mm)	1880 x 700 x 1320	Stainless Steel Type (Frame)	AISI 304	Voltage*	380-240 V
Net Weight (Kg)	161	Capacity	5 GN	Frequency	50 Hz.
Packaging Dimensions (mm)	1980 x 800 x 1420			Power (W)	4500
Interior Temperature °C	+30/+90				

Optional*

CRYSTAL®