

TECHNICAL SPECIFICATIONS

CHMG 270 SMT

Dimensions (mm)	1430 x 700 x 1100	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	150	Capacity	270 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1500 x 760 x 1250	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CHMG 280 SMT

Dimensions (mm)	1430 x 800 x 1100	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	165	Capacity	320 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1500 x 860 x 1250	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CHMG 370 SMT

Dimensions (mm)	1900 x 700 x 1100	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	190	Capacity	420 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1960 x 760 x 1250	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CHMG 380 SMT

Dimensions (mm)	1900 x 800 x 1100	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	210	Capacity	500 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1960 x 860 x 1250	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

