

TECHNICAL SPECIFICATIONS

CHMG 270 SPT-F

Dimensions (mm)	1430 x 700 x 1300	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	180	Capacity	270 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1500 x 760 x 1350	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CHMG 280 SPT-F

Dimensions (mm)	1430 x 800 x 1300	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	210	Capacity	320 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1500 x 860 x 1350	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CHMG 370 SPT-F

Dimensions (mm)	1900 x 700 x 1300	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	220	Capacity	420 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1960 x 760 x 1350	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

TECHNICAL SPECIFICATIONS

CHMG 380 SPT-F

Dimensions (mm)	1900 x 800 x 1300	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	260	Capacity	500 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1960 x 860 x 1350	Insulation Thickness(mm)	50	Power (W)	350
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*