

TECHNICAL SPECIFICATIONS

CHMT 280 S

Dimensions (mm)	1470 x 800 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	135	Capacity	360 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1540 x 860 x 1000	Insulation Thickness(mm)	50	Power (W)	300
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CHMT 280 D

Dimensions (mm)	1470 x 800 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	140	Capacity	360 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	1540 x 860 x 1000	Insulation Thickness(mm)	50	Power (W)	550
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CHMT 380 S

Dimensions (mm)	2000 x 800 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	180	Capacity	530 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2060 x 860 x 1000	Insulation Thickness(mm)	50	Power (W)	300
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CHMT 380 D

Dimensions (mm)	2000 x 800 x 850	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	185	Capacity	530 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2060x 860 x 1000	Insulation Thickness(mm)	50	Power (W)	600
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®