

TECHNICAL SPECIFICATIONS

CSM 360 S

Dimensions (mm)	2000 x 600 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	130	Capacity	225 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2060 x 660 x 750	Insulation Thickness(mm)	50	Power (W)	320
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CSM 360 D

Dimensions (mm)	2000 x 600 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	140	Capacity	225 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2060 x 660 x 750	Insulation Thickness(mm)	50	Power (W)	680
Interior Temperature °C	-10 /-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CSMG 370 S

Dimensions (mm)	2000 x 700 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	140	Capacity	270 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2060 x 760 x 750	Insulation Thickness(mm)	50	Power (W)	320
Interior Temperature °C	-2 /+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CSMG 370 D

Dimensions (mm)	2000 x 700 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	150	Capacity	270 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2060 x 760 x 750	Insulation Thickness(mm)	50	Power (W)	680
Interior Temperature °C	-10/-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CSMG 380 S

Dimensions (mm)	2000 x 800 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	150	Capacity	320 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2060 x 860 x 750	Insulation Thickness(mm)	50	Power (W)	320
Interior Temperature °C	-2/+8	Refrigerant Gas	R134		

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CSMG 380 D

Dimensions (mm)	2000 x 800 x 600	Stainless Steel Type	AISI 304	Voltage*	220-230 V
Net Weight (Kg)	160	Capacity	320 Lt	Frequency	50 Hz.
Packaging Dimensions (mm)	2060 x 860 x 750	Insulation Thickness(mm)	50	Power (W)	680
Interior Temperature °C	-10/-22	Refrigerant Gas	R404		

Optional*

CRYSTAL®