

# TECHNICAL SPECIFICATIONS

## CSM 460 S

Dimensions (mm)	<b>2400 x 600 x 600</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>155</b>	Capacity	<b>300 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2460 x 660 x 750</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## CSM 460 D

Dimensions (mm)	<b>2400 x 600 x 600</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>165</b>	Capacity	<b>300 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2460 x 660 x 750</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>750</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## CSMG 470 S

Dimensions (mm)	<b>2400 x 700 x 600</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>170</b>	Capacity	<b>370 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2460 x 760 x 750</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## CSMG 470 D

Dimensions (mm)	<b>2400 x 700 x 600</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>180</b>	Capacity	<b>370 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2460 x 760 x 750</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>750</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## CSMG 480 S

Dimensions (mm)	<b>2400 x 800 x 600</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>180</b>	Capacity	<b>440 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2460 x 860 x 750</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## CSMG 480 D

Dimensions (mm)	<b>2400 x 800 x 600</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>190</b>	Capacity	<b>440 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2460 x 860 x 750</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>750</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

CRYSTAL®