

# TECHNICAL SPECIFICATIONS

## STD 460 S

Dimensions (mm)	<b>2230 x 600 x 850</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>155</b>	Capacity	<b>460 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2290 x 660 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## STD 460 D

Dimensions (mm)	<b>2230 x 600 x 850</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>160</b>	Capacity	<b>460 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2290 x 660 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>680</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## STD 470 S

Dimensions (mm)	<b>2230 x 700 x 850</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>180</b>	Capacity	<b>540 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2290 x 760 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## STD 470 D

Dimensions (mm)	<b>2230 x 700 x 850</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>185</b>	Capacity	<b>540 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2290 x 760 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>680</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## STD 460 S-E

Dimensions (mm)	<b>2230 x 600 x 850</b>	Stainless Steel Type	<b>AISI 430</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>155</b>	Capacity	<b>460 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2290 x 660 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## STD 460 D-E

Dimensions (mm)	<b>2230 x 600 x 850</b>	Stainless Steel Type	<b>AISI 430</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>160</b>	Capacity	<b>460 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2290 x 660 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>680</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## STD 470 S-E

Dimensions (mm)	<b>2230 x 700 x 850</b>	Stainless Steel Type	<b>AISI 430</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>180</b>	Capacity	<b>540 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2290 x 760 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## STD 470 D-E

Dimensions (mm)	<b>2230 x 700 x 850</b>	Stainless Steel Type	<b>AISI 430</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>185</b>	Capacity	<b>540 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>2290 x 760 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>680</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

**CRYSTAL®**