

# TECHNICAL SPECIFICATIONS

## STD 160 S

Dimensions (mm)	<b>835 x 600 x 850</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>75</b>	Capacity	<b>100 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>875 x 640 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>275</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## STD 160 D

Dimensions (mm)	<b>835 x 600 x 850</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>80</b>	Capacity	<b>100 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>875 x 640 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>620</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## STD 170 S

Dimensions (mm)	<b>835 x 700 x 850</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>95</b>	Capacity	<b>125 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>875 x 740 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>275</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## STD 170 D

Dimensions (mm)	<b>835 x 700 x 850</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>100</b>	Capacity	<b>125 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>875 x 740 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>620</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

**Optional\***

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## STD 160 S-E

Dimensions (mm)	<b>835 x 600 x 850</b>	Stainless Steel Type	<b>AISI 430</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>75</b>	Capacity	<b>100 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>875 x 640 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>275</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

## STD 160 D-E

Dimensions (mm)	<b>835 x 600 x 850</b>	Stainless Steel Type	<b>AISI 430</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>80</b>	Capacity	<b>100 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>875 x 640 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>620</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## STD 170 S-E

Dimensions (mm)	<b>835 x 700 x 850</b>	Stainless Steel Type	<b>AISI 430</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>95</b>	Capacity	<b>125 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>875 x 740 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>275</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

## STD 170 D-E

Dimensions (mm)	<b>835 x 700 x 850</b>	Stainless Steel Type	<b>AISI 430</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>100</b>	Capacity	<b>125 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>875 x 740 x 1000</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>620</b>
Interior Temperature °C	<b>-10 /-22</b>	Refrigerant Gas	<b>R404</b>		

Optional\*

CRYSTAL®