

TECHNICAL SPECIFICATIONS

CBT 265 H

| | | | | | |
|---------------------------|-------------------------|--------------------------|-------------------------------|-----------|------------------|
| Dimensions (mm) | 540 x 770 x 1220 | Stainless Steel Type | AISI 304 | Voltage* | 220-230 V |
| Net Weight (Kg) | 70 | Capacity | GN 1/1 x 40 cm - 9 Pcs | Frequency | 50 Hz. |
| Packaging Dimensions (mm) | 630 x 830 x 1420 | Insulation Thickness(mm) | 70 | Power (W) | 800 |
| Interior Temperature °C | +75/+85 | | | | |

Optional*

CRYSTAL®

TECHNICAL SPECIFICATIONS

CBT 530 H

| | | | | | |
|---------------------------|-------------------------|--------------------------|--------------------------------|-----------|------------------|
| Dimensions (mm) | 540 x 770 x 1685 | Stainless Steel Type | AISI 304 | Voltage* | 220-230 V |
| Net Weight (Kg) | 90 | Capacity | GN 1/1 x 40 cm - 15 Pcs | Frequency | 50 Hz. |
| Packaging Dimensions (mm) | 600 x 830 x 1885 | Insulation Thickness(mm) | 70 | Power (W) | 800 |
| Interior Temperature °C | +75/+85 | | | | |

Optional*

CRYSTAL®