

# TECHNICAL SPECIFICATIONS

# CBT 350 H

Dimensions (mm)	<b>765 x 890 x 1035</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>70</b>	Capacity	<b>GN 1/1 x 40 cm - 10 Pcs</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>825 x 950 x 1235</b>	Insulation Thickness(mm)	<b>70</b>	Power (W)	<b>800</b>
Interior Temperature °C	<b>+75/+85</b>				

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

# CBT 700 H

Dimensions (mm)	<b>765 x 890 x 1745</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>105</b>	Capacity	<b>GN 1/1 x 40 cm - 21 Pcs</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>825 x 950 x 1945</b>	Insulation Thickness(mm)	<b>70</b>	Power (W)	<b>1550</b>
Interior Temperature °C	<b>+75/+85</b>				

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

# CBT 1400 H

Dimensions (mm)	<b>1480 x 890 x 1745</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>185</b>	Capacity	<b>GN 1/1 x 40 cm - 42 Pcs</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>1540 x 950 x 1945</b>	Insulation Thickness(mm)	<b>70</b>	Power (W)	<b>2550</b>
Interior Temperature °C	<b>+75/+85</b>				

Optional\*

**CRYSTAL®**