

# TECHNICAL SPECIFICATIONS

# CHMG 270 SPT

Dimensions (mm)	<b>1430 x 700 x 1300</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>200</b>	Capacity	<b>270 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>1500 x 760 x 1350</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

# CHMG 280 SPT

Dimensions (mm)	<b>1430 x 800 x 1300</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>230</b>	Capacity	<b>320 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>1500 x 860 x 1350</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

**CRYSTAL®**

# TECHNICAL SPECIFICATIONS

# CHMG 370 SPT

Dimensions (mm)	<b>1900 x 700 x 1300</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>240</b>	Capacity	<b>420 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>1960 x 760 x 1350</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®

# TECHNICAL SPECIFICATIONS

# CHMG 380 SPT

Dimensions (mm)	<b>1900 x 800 x 1300</b>	Stainless Steel Type	<b>AISI 304</b>	Voltage*	<b>220-230 V</b>
Net Weight (Kg)	<b>280</b>	Capacity	<b>500 Lt</b>	Frequency	<b>50 Hz.</b>
Packaging Dimensions (mm)	<b>1960 x 860 x 1350</b>	Insulation Thickness(mm)	<b>50</b>	Power (W)	<b>350</b>
Interior Temperature °C	<b>-2/+8</b>	Refrigerant Gas	<b>R134</b>		

Optional\*

CRYSTAL®